

DEUCE CAFÉ COUNTER

Interactive



DEU-36-CC

40"D X 36"W X 38"H

DEUCE CAFÉ COUNTER



DEU-25-CC



DEU-36-CC



DEU-48-CC



DEU-60-CC

DEUCE CAFÉ COUNTER

- Bench base is 3/4" black melamine with 3mm black PVC edge.
- Bench back is 3/4" engineered wood with high-pressure laminate surfaces and 3mm PVC edges or wood (oak or maple) veneer surfaces with 3mm wood edges.
- 3-1/2" thick upholstery foam for comfort.
- Frame assembly is fabricated of 1.25" square 16-gauge powder coated steel tubing. End frames are welded assemblies and bolt together with spanners.
- Legs are fitted with leveling glides.

To Order, Choose Finish Selections & Options

Upholstery: Choose fabric for seat and back cushion.

Frame: Choose powder coat option for steel frame.

WorkSurface: Choose a high-pressure laminate for work surface.

Edges: Choose PVC for edges.

Bench Base and Back Panels: Select from our high-pressure laminate, wood veneer or melamine selection (Sprayon available on veneer).

See **mediatechnologies'** Finish and Color Guide for options at www.mediatechnologies.com.

DEUCE CAFÉ COUNTER STANDARD SIZES

MODEL	DEPTH"	WIDTH"	OVERALL HEIGHT"	SHELF HEIGHT"	SEAT HEIGHT"
DEU-25-CC	40	25	38	36	18
DEU-36-CC	40	36	38	36	18
DEU-48-CC	40	48	38	36	18
DEU-60-CC	40	60	38	36	18

General Specifications

Upholstered Seat and Back: Seat cushions are 3-1/2" high-density upholstery grade foam on an 11/16" engineered wood frame. Vinyl and fabric upholstery is available. Can use a combination of both. Upholstered seat and back cushions are fastened to bench base and bench back with hook and loop fasteners.

Bench Base and Bench Back Panels: Bench bottom is 3/4" black melamine and bench back panel is 11/16" engineered wood. back panel can be finished in HPL with PVC edges or veneer with wood edges. Veneer option can accept Sprayon finish. Back panel is bolted to frame assembly with metal-to-metal connection. Base panel assembly is bolted to frame assembly with metal-to-metal connection.

Café Height Counter Top: 12" deep countertop is 1" thick veneer core plywood with .050" HPL worksurface with .030 phenolic backer and 3mm PVC edges. Countertop support bracket is 11-gauge flat steel with 1/2" steel rod.

Frame Assembly: The frame assembly is fabricated of 1.25" square powder coated steel tubing. End frames are welded assemblies. Bolt together spanners complete the seat frame assembly. The bottom of each leg is fitted with a threaded weldnut and a 1-7/8" black leveling glide.



cs-deucecafe-180524

892 Industrial Park Drive
 Shelby, MI 49455
 P: 231.861.2194
 F: 231.861.6678
www.mediatechnologies.com
sales@mediatechnologies.com

