

DRIFT

Benches



DFTB-42-1819-TOTO-L-MOB

19"D X 42"W X 18"H

DRIFT



DFTB-42-1819-TOTO-L-MOB

DRIFT BENCH

- Available in two storage base options: Open Storage and Open Tote Storage. Storage base is only available on one side.
- Pairs with Drift mobile shelving and storage.
- Comfortable 1-1/2" thick upholstered seat cushion.
- Available in your choice of oak or maple veneer, high-pressure laminate or melamine.
- Swivel casters for added mobility.

DRIFT BENCH OPEN STORAGE STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
DFTB-42-1819-OS-T-MOB	19	42	18
DFTB-42-1819-OS-L-MOB	19	42	18
DFTB-42-1819-OS-M-MOB	19	42	18
DFTB-42-1819-OS-O-MOB	19	42	18

General Specifications

End/Intermediate Panels: All end and intermediate panels are un-detailed 3/4" engineered wood with high pressure laminate, melamine or veneer on both faces; exposed laminate panel edges are banded with 3mm PVC, veneer panel edges are banded with 1/8" w wood banding. Edges and corners radiused 1/8". Vertical panels are machined for the mounting of tote rails on Open Tote Storage units. One (1) mobile storage unit is constructed of two (2) end panels and one (1) or two (2) intermediate panels. The Open Storage model has two storage compartments divided by one vertical intermediate panel. Each compartment will have one adjustable shelf. The Open Tote Storage model has three compartments with two vertical dividers.

Top: The top panel is 1" thick engineered wood with high pressure laminate, melamine or veneer faces. The laminate panel edges are banded with 3mm PVC, veneer panel edges are banded with 1/8" w wood banding. The top is attached with pre-glued dowels. The upholstered seat cushion assembly is 1-1/2" of upholstery foam on a 3/4" cushion backer. The seat cushion assembly is fastened to the top panel with screws.

To Order, Choose Finish Selections & Options

Base Cabinet: Choose from our selection of oak or maple veneers, high pressure laminate or melamine.

Edges: Choose from our selection of wood or PVC edges.

Seat: Choose from our selection of graded fabrics.

See **mediatechnologies'** finish selections at <https://www.mediatechnologies.com/resources/finishes>
View our fabric choices at <https://www.mediatechnologies.com/resources/fabrics>

DRIFT BENCH OPEN TOTE STORAGE STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
DFTB-42-1819-TOTO-T-MOB	19	42	18
DFTB-42-1819-TOTO-L-MOB	19	42	18
DFTB-42-1819-TOTO-M-MOB	19	42	18
DFTB-42-1819-TOTO-O-MOB	19	42	18

Base: The base is 1" thick engineered wood with a high pressure laminate, melamine or veneer face and a .030 phenolic backer; exposed laminate panel edges are banded with 3mm PVC, veneer panel edges are banded with 1/8" w wood banding. Edges and corners radiused 1/8". The base is fastened to the vertical panels with pre-glued dowels and screws. 75mm locking swivel casters with thermoplastic elastomer treads are bolted to the bottom of the base using 5/16" - 18 machine bolts. Casters are located at the four corners of the base.

Back Panel: Back is 3/4" thick engineered wood with a high pressure laminate, melamine or veneer faces.

Tote Rails (on Open Tote Storage Models): TOTR tote rails are mounted on the inside faces of the end panels and both faces of the intermediate panels and allow totes to be fully removable. Tote rail type and spacing is suitable for the use of TOT03- & TOT06- totes. *Totes are not included and can be found at: <https://www.mediatechnologies.com/product/totes>*

Note: DRIFT BENCHES models ship assembled.



cs-driftbench-221227

892 Industrial Park Drive
Shelby, MI 49455
P: 231.861.2194
F: 231.861.6678
www.mediatechnologies.com
sales@mediatechnologies.com

PURE MICHIGAN®